

ENFRIADOR DE AGUA EAN258AC HASTA EAN7008AC



LINEA INDUSTRIAL
ROBUSTEZ Y DISEÑO

DATOS TECNICOS

Modelo	Capacidad Frig/h			Compr. HP	Caudal agua M3/h	Dimensiones Mts		
	7 °C	10 °C	15 °C			Base		Alt
EAN 258 AC	25800	27864	31218	11	5,57	1,04	1,68	1,50
EAN 584 AC	58480	63158	70761	24	12,63	1,08	2,11	1,87
EAN 1168 AC	116800	126317	141522	48	25,26	2,11	2,66	1,87
EAN 1752 AC	175200	189475	212283	72	37,90	2,11	4,24	1,87
EAN 2336 AC	233600	252634	283044	96	50,53	4,72	2,66	1,87
EAN 2920 AC	292000	315792	353805	120	63,16	4,72	3,74	1,87
EAN 3504 AC	350400	378950	424566	144	75,79	4,72	3,74	1,87
EAN 4088 AC	408800	442109	495327	168	88,42	4,72	4,82	1,87
EAN 4672 AC	467200	505267	566088	192	101,05	4,72	4,82	1,87
EAN 5256 AC	525600	568426	636849	216	113,69	4,72	5,90	1,87
EAN 5840 AC	584000	631584	707610	240	126,32	4,72	5,90	1,87
EAN 6424 AC	642400	694742	778371	264	138,95	4,72	6,98	1,87
EAN 7008 AC	700800	757901	849132	288	151,58	4,72	6,98	1,87

Capacidades referidas a temperatura ambiente 35 °C

Osmi se reserva el derecho de realizar modificaciones sin previo aviso

OSMI SRL Basavilbaso 1060 Sarandí Bs.As. Argentina 4203-2000 Rot. www.osmi.com.ar