

ENFRIADORES DE AGUA A TORNILLO POR AGUA



LINEA INDUSTRIAL
ROBUSTEZ Y DISEÑO

DATOS TÉCNICOS

MODELO	Capacidad frigorífica a 7 °C			Consumo KW
	TR	KW	Kcal/h	
EANT220WC	62.6	220	189200	44
EANT260WC	73.9	260	223600	53
EANT340WC	96.7	340	292400	70
EANT380WC	108.1	380	326800	76
EANT430WC	122.3	430	369800	88
EANT480WC	136.5	480	412800	96
EANT560WC	159.3	560	481600	112
EANT660WC	187.7	660	567600	132
EANT760WC	216.2	760	653600	152
EANT900WC	256.0	900	774000	180
EANT960WC	273.0	960	825600	192
EANT1120WC	318.5	1120	963200	224
EANT1320WC	375.4	1320	1135200	264
EANT1520WC	432.3	1520	1307200	308
EANT1660WC	472.1	1660	1427600	336
EANT1800WC	511.9	1800	1548000	362
EANT1920WC	546.1	1920	1651200	388
EANT2080WC	591.6	2080	1788800	420
EANT2240WC	637.1	2240	1926400	459
EANT2480WC	705.3	2480	2132800	498
EANT2720WC	773.6	2720	2339200	548
EANT3100WC	881.7	3100	2666000	624